

# ASM Handbook<sup>®</sup>

---

## Volume 5 Surface Engineering

Prepared under the direction of the  
ASM International Handbook Committee

Volume Chairpersons

**Catherine M. Cotell**

**James A. Sprague**

**Fred A. Smidt, Jr.**

**Scott D. Henry**, Manager of Handbook Development

**Grace M. Davidson**, Manager of Handbook Production

**Steven R. Lampman**, Technical Editor

**Faith Reidenbach**, Chief Copy Editor

**Tina M. Lucarelli**, Editorial Assistant

**Randall L. Boring**, Production Coordinator

**Ann-Marie O'Loughlin**, Production Coordinator

**William W. Scott, Jr.**, Director of Technical Publications

Editorial Assistance

**Kathleen S. Dragolich**

**Kelly Ferjutz**

**Nikki D. Wheaton**

**Mara S. Woods**



NOT TO LEAVE  
ROESCH LIBRARY  
UNIVERSITY OF DAYTON

Copyright © 1994  
by  
ASM International®  
All rights reserved

No part of this book may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the written permission of the copyright owner.

First printing, December 1994

This book is a collective effort involving hundreds of technical specialists. It brings together a wealth of information from world-wide sources to help scientists, engineers, and technicians solve current and long-range problems.

Great care is taken in the compilation and production of this Volume, but it should be made clear that NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE GIVEN IN CONNECTION WITH THIS PUBLICATION. Although this information is believed to be accurate by ASM, ASM cannot guarantee that favorable results will be obtained from the use of this publication alone. This publication is intended for use by persons having technical skill, at their sole discretion and risk. Since the conditions of product or material use are outside of ASM's control, ASM assumes no liability or obligation in connection with any use of this information. No claim of any kind, whether as to products or information in this publication, and whether or not based on negligence, shall be greater in amount than the purchase price of this product or publication in respect of which damages are claimed. THE REMEDY HEREBY PROVIDED SHALL BE THE EXCLUSIVE AND SOLE REMEDY OF BUYER, AND IN NO EVENT SHALL EITHER PARTY BE LIABLE FOR SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES WHETHER OR NOT CAUSED BY OR RESULTING FROM THE NEGLIGENCE OF SUCH PARTY. As with any material, evaluation of the material under end-use conditions prior to specification is essential. Therefore, specific testing under actual conditions is recommended.

Nothing contained in this book shall be construed as a grant of any right of manufacture, sale, use, or reproduction, in connection with any method, process, apparatus, product, composition, or system, whether or not covered by letters patent, copyright, or trademark, and nothing contained in this book shall be construed as a defense against any alleged infringement of letters patent, copyright, or trademark, or as a defense against liability for such infringement.

Comments, criticisms, and suggestions are invited, and should be forwarded to ASM International.

#### Library of Congress Cataloging-in-Publication Data

ASM International

ASM handbook.

Includes bibliographical references and indexes.

Contents: v.1. Properties and selection—iron, steels, and high-performance alloys—v.2. Properties and selection—nonferrous alloys and special—purpose materials—[etc.]—v.3. Surface engineering

I. Metals—Handbooks, manuals, etc.  
I. ASM International. Handbook Committee.

II Metals handbook.  
TA459.M43 1990 620.1'6 90-115  
ISBN 0-87170-377-7 (v.1)  
SAN 204-7586

ISBN 0-87170-384-X

ASM International®  
Materials Park, OH 44073-0002

Printed in the United States of America

# Phosphate Coatings

PHOSPHATE COATING is the treatment of iron, steel, galvanized steel, or aluminum with a dilute solution of phosphoric acid and other chemicals in which the surface of the metal, reacting chemically with the phosphoric acid media, is converted to an integral, mildly protective layer of insoluble crystalline phosphate. The weight and crystalline structure of the coating and the extent of penetration of the coating into the base metal can be controlled by:

- Method of cleaning before treatment
- Use of activating rinses containing titanium and other metals or compounds
- Method of applying the solution
- Temperature, concentration, and duration of treatment
- Modification of the chemical composition of phosphating solution

The method of applying phosphate coatings is usually determined by the size and shape of the article to be coated. Small items, such as nuts, bolts, screws, and stampings, are coated in tumbling barrels immersed in phosphating solution. Large fabricated articles, such as refrigerator cabinets, are spray coated with solution while on conveyors. Automobile bodies are sprayed with or immersed in phosphating solution. Steel sheet and strip can be passed continuously through the phosphating solution or can be sprayed.

Phosphate coatings range in thickness from less than 3 to 50  $\mu\text{m}$  (0.1 to 2 mil). Coating weight (grams per square meter of coated area), rather than coating thickness, has been adopted as the basis for expressing the amount of coating deposited.

## Phosphate Coatings

Three principal types of phosphate coatings are in general use: zinc, iron, and manganese. A fourth type, lead phosphate, more recently introduced, is operated at ambient temperatures.

Zinc phosphate coatings encompass a wide range of weights and crystal characteristics, ranging from heavy films with coarse crystals to ultrathin microcrystalline deposits. Zinc phosphate coatings vary from light to dark gray in color. Coatings are darker as the carbon content of the underlying steel increases, as the ferrous content of the coating increases, as heavy metal ions are incorporated into the phosphating solution, or as the substrate metal is

acid pickled prior to phosphating. Zinc phosphating solutions containing active oxidizers usually produce lighter-colored coatings than do solutions using milder accelerators.

Zinc phosphate coatings can be applied by spray, immersion, or a combination of the two. Coatings can be used for any of the following applications of phosphating: base for paint or oil; aid to cold forming, tube drawing, and wire drawing; increasing wear resistance; or rustproofing. Spray coatings on steel surfaces range in weight from 1.08 to 10.8  $\text{g/m}^2$  ( $3.5 \times 10^{-3}$  to  $3.5 \times 10^{-2}$   $\text{oz/ft}^2$ ); immersion coatings, from 1.61 to 43.0  $\text{g/m}^2$  ( $5.28 \times 10^{-3}$  to 0.141  $\text{oz/ft}^2$ ).

Iron phosphate coatings were the first to be used commercially. Early iron phosphating solutions consisted of ferrous phosphate/phosphoric acid used at temperatures near boiling and produced dark gray coatings with coarse crystals. The term *iron phosphate coatings* refers to coatings resulting from alkali-metal phosphate solutions operated at pH in the range of 4.0 to 5.0, which produce exceedingly fine crystals. The solutions produce an amorphous coating consisting primarily of iron oxides and having an interference color range of iridescent blue to reddish-blue color.

A typical formulation for an iron phosphate bath is (Ref 1):

| Component                     | Composition, % |
|-------------------------------|----------------|
| Phosphate salts               | 12-15          |
| Phosphoric acid               | 3-4            |
| Molybdate accelerator         | 0.25-0.50      |
| Detergents (anionic/nonionic) | 8-10           |

Basically, then, iron phosphate formulations consist of primary phosphate salts and accelerators dissolved in a phosphoric acid solution. It is the acid that initiates the formation of a coating on a metal surface. When acid attacks the metal and begins to be consumed, solution pH at the metal surface rises slightly. This is what causes the primary phosphate salts to drop out of solution and react with the metal surface, forming a crystalline coating.

All iron phosphate conversion coatings are composed of partially neutralized phosphoric acid. But all iron phosphates are not created equal. Other ingredients, such as the specific accelerator used (Table 1), hold part of the key.

Although iron phosphate coatings are applied to steel to provide a receptive surface for the bonding of fabric, wood, and other materials,

their chief application is as a base for subsequent films of paint. Processes that produce iron phosphate coatings are also available for treatment of galvanized and aluminum surfaces. Iron phosphate coatings have excellent adherence and provide good resistance to flaking from impact or flexing when painted. Corrosion resistance, either through film or scribe undercut, is usually less than that attained with zinc phosphate. However, a good iron phosphate coating often outperforms a poor zinc phosphate coating.

Spray application of iron phosphate coatings is most frequently used, although immersion application also is practical. The accepted range of coating weights is 0.21 to 0.86  $\text{g/m}^2$  ( $6.9 \times 10^{-4}$  to 0.26  $\text{oz/ft}^2$ ). Little benefit is derived from exceeding this range, and coatings of less than 0.21  $\text{g/m}^2$  ( $6.9 \times 10^{-4}$   $\text{oz/ft}^2$ ) are likely to be nonuniform or discontinuous. Quality iron phosphate coatings are routinely deposited at temperatures from 25 to 65 °C (80 to 150 °F) by either spray or immersion methods.

Manganese phosphate coatings are applied to ferrous parts (bearings, gears, and internal combustion engine parts, for example) for break-in and to prevent galling. These coatings are usually dark gray. However, because almost all manganese phosphate coatings are used as an oil base and the oil intensifies the coloring, manganese phosphate coatings are usually black in appearance. In some instances, a calcium-modified zinc phosphate coating can be substituted for manganese phosphate to impart break-in and antirattle properties.

Manganese phosphate coatings are applied only by immersion, requiring times ranging from 5 to 30 min. Coating weights normally vary from 5.4 to 32.3  $\text{g/m}^2$  ( $1.8 \times 10^{-2}$  to 9.83  $\text{oz/ft}^2$ ), but can be greater if required. The manganese phosphate coating usually preferred is tight and fine-

Table 1 Effect of accelerators on the weight of an iron phosphate coating

| Accelerator | Surface treated                                | Coating weight |                                 |
|-------------|--|----------------|---------------------------------|
|             |  | $\text{g/m}^2$ | $\text{oz/ft}^2 \times 10^{-3}$ |
| ...         | Steel only                                     | 0.11-0.27      | 0.35-0.88                       |
| Metallic    | Mixed metal loads, ferrous, zinc, and aluminum | 0.22-0.38      | 0.71-1.24                       |
| Oxidizer    | High-quality steel only                        | 0.43-0.86      | 1.41-2.82                       |

Source: Ref 2

Table 2 Accelerators used in phosphate coating processes

| Type of accelerator           | Accelerator source  | Effective concentration |         |                         | Optimum operating conditions                                     |                |         | Advantages | Limitations   |
|-------------------------------|---|-------------------------|---------|-------------------------|--|----------------|---------|------------|---|
|                               |   | %                       | g/L     | lb/gal $\times 10^{-3}$ | Ratio  | Temperature °C | °F      |            |   |
| NO <sub>3</sub> <sup>-</sup>  | NaNO <sub>3</sub> , Zn(NO <sub>3</sub> ) <sub>2</sub> , Ni(NO <sub>3</sub> ) <sub>2</sub> | 1-3                     | ...     | ...                     | High NO <sub>3</sub> <sup>-</sup> :PO <sub>4</sub> <sup>3-</sup> | 65-93          | 149-199 | ...        | Lower sludge.   |
| NO <sub>2</sub> <sup>-</sup>  | NaNO <sup>+</sup>   | ...                     | 0.1-0.2 | 0.8-1.7                 | NO <sub>2</sub> <sup>-</sup> :NO = 1:1                           | (a)            | (a)     | Continuous | Affords rapid processing even at low temperatures.  |
| ClO <sub>3</sub> <sup>-</sup> | Zn(ClO <sub>3</sub> ) <sub>2</sub>  | 0.5-1                   | ...     | ...                     | ...  | (a)            | (a)     | Continuous | Stable in liquid concentrates. Can be used for bath makeup and replenishment. Overcomes the white staining problem. |
| H <sub>2</sub> O <sub>2</sub> | H <sub>2</sub> O <sub>2</sub>   | ...                     | 0.05    | 0.4                     | ...  | (a)            | (a)     | ...        | Low coating weight. No harmful products. Free from staining.  |
| Perborate                     | Sodium perborate  | ...                     | ...     | ...                     | ...  | (a)            | (a)     | ...        | No separate neutralizer is required. Good corrosion resistance.   |
| Nitroguanidine                | Nitroguanidine  | ...                     | ...     | ...                     | ...  | 55             | 130     | ...        | Neither the accelerator nor its reduction products are corrosive.   |

(a) Low temperature. Source: Ref 3

grain, rather than loose and coarse-grain. However, desired crystal size varies with service requirements. In many instances, the crystal is refined as the result of some pretreatment (certain types of cleaners and/or conditioning agents based on manganese phosphate) of the metal surface.

Manganese-iron phosphate coatings are usually formed from high-temperature baths from 90 to 95 °C (190 to 200 °F).

### Composition of Phosphate Coating

All phosphate coatings are produced by the same type of chemical reaction: the acid bath, containing the coating chemicals, reacts with the metal to be coated, and at the interface, a thin film of solution is neutralized because of its attack on the metal. In the neutralized solution, solubility of the metal phosphates is reduced, and they precipitate from the solution as crystals. Crystals are then attracted to the surface of the metal by the normal electrostatic potential within the metal, and they are deposited on the cathodic sites.

When an acid phosphate reacts with steel, two types of iron phosphate are produced: a primary phosphate, which enters the coating; and a secondary phosphate, which enters the solution as a soluble iron compound. If this secondary ferrous phosphate were oxidized to a ferric phosphate, it would no longer be soluble and would precipitate from the bath. Oxidizing agents are incorporated to remove the soluble secondary ferrous phosphate because the ferrous phosphate inhibits coating formation.

Although all phosphating baths are acid in nature and to some extent attack the metal being coated, hydrogen embrittlement seldom occurs as a result of phosphating. This is primarily because all phosphating baths contain depolarizers or oxidizers that react with the hydrogen as it is formed

and render it harmless to the metal. In some instances, however, zinc-phosphate processes, intended for use with rust-inhibiting oils for corrosion resistance or manganese-phosphate treatments, can cause hydrogen embrittlement because they may contain a minimum amount of depolarizers and oxidizers. A dwell time before use or mild heating may be needed to relieve embrittlement.

The acidity of phosphating baths varies, depending on the type of phosphating compound and its method of application. Immersion zinc phosphating baths operate in a pH range of 1.4 to 2.4, whereas spray zinc phosphating solutions can operate at a pH as high as 3.4, depending on the bath temperature. Iron phosphating baths usually operate at a pH of 3.8 to 5. Manganese phosphating baths operate in a pH range comparable to that of the immersion zinc phosphating solutions. Lead-phosphate solutions are usually more acidic than any of the others.

Zinc, iron, and manganese phosphating baths usually contain an accelerator, which can range from a mild oxidant, such as nitrate, to one of the more vigorous nitrite, chlorate, peroxide, or organic sulfonic acids (Table 2). The purposes of these accelerators are to speed up the rate of coating, to oxidize ferrous iron, and to reduce crystal size. This is accomplished because of the ability of the accelerators to oxidize the hydrogen from the surface of the metal being coated. Phosphating solution can then contact the metal continuously, permitting completeness of reaction and uniformity of coverage. Accelerators have an oxidizing effect on the dissolved iron in the bath, thus extending the useful life of the solution. Some zinc and iron phosphating processes rely on oxygen from the air as the accelerator. Zinc phosphating baths for aluminum usually contain complex or free fluorides to accelerate coating formation and to block the coating-inhibiting effect of soluble aluminum.

### Applications

On the basis of pounds of chemicals consumed or tons of steel treated, the greatest use of phosphate coatings is as a base for paint. Phosphate coatings are also used to provide:

- A base for oil or other rust-preventive material
- Lubricity and resistance to wear, galling, or scoring of parts moving in contact, with or without oil
- A surface that facilitates cold forming
- Temporary or short-time resistance to mild corrosion
- A base for adhesives in plastic-metal laminations or rubber-to-metal applications

### Phosphate Coatings as a Base for Paint

The useful life of any painted metal article depends mainly on the durability of the organic coating itself and the adherence of the film to the surface on which it is applied. The primary function of any protective coating of paint is to prevent corrosion of the base metal in the environment in which it is used. To accomplish this purpose, the method of preparing the metal should reduce the activity of the metal surface, so that underfilm corrosion is prevented at the interface between paint and metal.

When used as a base for paint films, phosphate coatings promote good paint adhesion, increase the resistance of the films to humidity and water soaking, and substantially retard the spread of any corrosion that may occur. A phosphate coating retards the amount of corrosion creep, because the coating is a dielectric film that insulates the active anode and cathode centers existing over the entire surface of the base metal. By insulating these areas, corrosion of the surface is arrested or at least substantially retarded.

# PROTECTIVE COATINGS for Metals

by

R. M. BURNS

*Formerly Director of  
Chemical and Metallurgical Research  
Bell Telephone Laboratories, Inc.*

and

W. W. BRADLEY

*Member of the Technical Staff  
Bell Telephone Laboratories, Inc.*

SECOND EDITION



REINHOLD PUBLISHING CORPORATION

*Publishers of Chemical Engineering Catalog, Chemical Materials Catalog, Materials  
& Methods, Automatic Control, Progressive Architecture, and Advertising Manage-  
ment of American Chemical Society*

430 Park Avenue, New York

# General Introduction

## American Chemical Society's Series of Chemical Monographs

By arrangement with the Interallied Conference of Pure and Applied Chemistry, which met in London and Brussels in July, 1919, the American Chemical Society was to undertake the production and publication of Scientific and Technologic Monographs on chemical subjects. At the same time it was agreed that the National Research Council, in cooperation with the American Chemical Society and the American Physical Society, should undertake the production and publication of Critical Tables of Chemical and Physical Constants. The American Chemical Society and the National Research Council mutually agreed to care for these two fields of chemical progress. The American Chemical Society named as Trustees, to make the necessary arrangements of the publication of the Monographs, Charles L. Parsons, secretary of the Society, Washington, D. C.; the late John E. Teeple, then treasurer of the Society, New York; and the late Professor Gellert Alleman of Swarthmore College. The Trustees arranged for the publication of the ACS Series of (a) Scientific and (b) Technological Monographs by the Chemical Catalog Company, Inc. (Reinhold Publishing Corporation, successor) of New York. The Council of the American Chemical Society, acting through its Committee on National Policy, appointed editors (the present list of whom appears at the close of this sketch) to select authors of competent authority in their respective fields and to consider critically the manuscripts submitted.

The first Monograph of the Series appeared in 1921. After twenty-three years of experience certain modifications of general policy were indicated. In the beginning there still remained from the preceding five decades a distinct though arbitrary differentiation between so-called "pure science" publications and technologic or applied science literature.

By 1944 this differentiation was fast becoming nebulous. Research in private enterprise had grown apace and not a little of it was pursued on the frontiers of knowledge. Furthermore, most workers in the sciences were coming to see the artificiality of the separation. The methods of both groups of workers are the same. They employ the same instru-

Copyright 1955 by

REINHOLD PUBLISHING CORPORATION

All rights reserved

Library of Congress Catalog Card Number: 55-6822

Printed in the United States of America

## 16. Chemical Conversion and Anodized Coatings

Within recent years protective coatings that are neither of the metallic nor the paint type have come into prominence. They provide an insulating barrier of exceedingly low solubility between a metal and its environment through conversion of the metal surface into a corrosion-resistant, nonreactive form. The conversion consists of a chemical or electrochemical modification of the metal surface so that the coating so formed is an integral part of the parent metal. This is in contrast to paints and most metallic coatings which require no chemical combination with the basis metal. Most of these coatings lend themselves particularly to impregnation with paints, enamels, and lacquers, and it is here that they find their widest applications. The protection provided is enhanced many-fold through improvement of adhesion, restriction of moisture penetration, and prevention of the spread of underfilm corrosion. Most such films are absorbent, providing an ideal base for protective oils and waxes. In some cases conversion coatings are used without further treatments.

The metals for which surface conversion treatments have attained marked commercial significance are iron and steel, and aluminum, zinc, and stainless steel are finished in this manner.

The techniques in common use today for forming this type of protective coating fall into two general categories (1) chemical dip, spray, or brush and (2) electrolytic methods. In chemical dip reactions an oxidized form of the metal being treated or of a metal ion present in the bath is formed on the metal surface, the operating conditions being controlled to provide the properties required for the intended service. This category includes phosphating, used generally to provide a paint base on steel and zinc; chromating, of value in protecting zinc and cadmium in humid atmospheres; and chemical oxide coatings, used to enhance the corrosion resistance and appearance of aluminum, steel, and copper alloy parts. Some oxidizing treatments for forming a paint base on magnesium also

fall in this category. Electrolytic processes, as the name implies, depend on an externally applied voltage to promote the formation of protective films in a suitable electrolyte. The foremost application of this technique is in the anodizing of aluminum alloys. Electrolytic methods are also used for several magnesium treatments.

### PHOSPHATING

Phosphating processes are used to provide protective coatings for a wide variety of iron and steel products. Zinc is also phosphated in commercially significant quantities, and, to a lesser extent, aluminum alloys, cadmium, and tin. For most applications the phosphate coating is not itself sufficiently protective, but serves as an excellent base for impregnation with paint, enamel, lacquer, oils, or waxes. Parts which are to be treated with oil or wax are given a thick phosphate coat. Nuts and bolts are illustrative of such articles. The relatively heavy, absorbent coating retains oil for extended periods of time, excluding moisture and providing lubrication. Surfaces that are to be painted are given a "fast" treatment during which a thin phosphate coating is deposited. Here the coating serves to anchor the paint film and suppress corrosion. Phosphating offers the advantage of requiring only simple and relatively inexpensive equipment. Moreover, coating formation depends only on contact between the work and the bath; hence, intricate parts offer no particular problem. The development of "fast" solutions, with treatment times of a minute or less, permits the use of spray application, particularly advantageous in treating bulky articles or in coating composite units after assembly, thus avoiding damage to the coating during assembly.

Historically, phosphating is of ancient origin. There is evidence that the use of phosphates for the protection of certain iron articles was known to the Romans in the third century A.D.<sup>1</sup> In 1869 it was observed<sup>2</sup> that rusting of the metallic parts of women's corsets was retarded by treating them with phosphoric acid. The first important commercial application of phosphate coatings followed the proposal of Coslett in 1908 to treat iron and steel parts in a solution of phosphoric acid and ferrous sulfate in definite proportions.<sup>3</sup> Later Coslett substituted zinc sulfate for the ferrous sulfate, and in 1918 it was found by the Parker Company<sup>4</sup> that

<sup>1</sup> Jacobi, L., "Das Römische Salzbild von der Höhe," pp. 158, 201, 202, Homburg, 1897; Macchia O., *Ind. Mecanica*, 17, 617 (1906).

<sup>2</sup> Tanner, R. R., *Monthly Rev. Am. Electroplater's Soc.*, 21, No. 5, 20 (1904).


<sup>3</sup> Thornton-Murray, M., *Engineering*, 85, 870 (1908); Blassitt, E., *Metal Ind. (N. Y.)*, 9, 207 (1911).

<sup>4</sup> *Chem. & Met. Eng.*, 18, 264 (1918); Edelmann, L. E., *Chem. & Met. Eng.*, 21, 787 (1919); *Raw Materials*, 5, 438 (1922).



the character of the coating was improved by the use of a solution of primary manganous phosphate. In this process, which came to be known as "Parkerizing," manganese dioxide was added to the bath, it being claimed that oxidation of at least some of the phosphate to the form of ferric phosphate was essential. The time required for treatment was usually from 3 to 4 hours. While the Coslett process known as "Coslettizing" was rather widely used in England for phosphating the steel parts of bicycles and other articles, neither it nor the original Parkerizing process was suited to the needs of the rapidly expanding finishing industry.

The Parker process was improved in 1926 by the adoption of manganese dihydrogen phosphate for the processing solution. This made possible a reduction in time of treatment. Somewhat later a further reduction in processing time to about 10 minutes was effected by incorporating a small percentage of a copper salt in the bath. This permitted the use of the process in a conveyORIZED or line finishing system.<sup>5</sup> The increasing use of phosphate coatings as a base for paint was reflected in the name "bonderizing," given to the improved process.<sup>6</sup> Still later improvements have been in the direction of time reduction and spray application.


Phosphate coatings consist of crystalline salts of the metal being treated or of metal ions added to the phosphating solution. Although the detailed compositions of phosphate baths are largely proprietary and the exact reactions complex, simple equations may be used to illustrate the formation of the phosphate coatings. A bath commonly used to coat iron or steel is made from primary zinc phosphate in aqueous solution with phosphoric acid which ultimately yields the tertiary salt, a reaction promoted by elevated temperature and agitation.



The bath is so balanced that the tertiary salt is near saturation. Iron, when immersed in such a bath, is attacked by the free phosphoric acid, giving primary and secondary iron phosphate, and liberating hydrogen on cathodic areas.



As the pH at the metal-solution interface is increased, the solubility products of the secondary and tertiary salts are exceeded. The over-all reaction is illustrated by:



<sup>5</sup> U. S. Patent 1,888,189.

<sup>6</sup> Darney, V. M., *Ind. Eng. Chem.*, 27, 1142 (1935).



The crystalline layer formed is largely the insoluble tertiary zinc phosphate, together with a small amount of secondary iron phosphate. Recent evidence indicates that some iron from the solution becomes an integral part of the coating during the process.<sup>7</sup> The proportion of iron to zinc is dependent on the method of application, solution composition, temperature, and time of processing.

The solution composition is critical in that too much free acid results only in pickling of the steel surface,<sup>8</sup> while too little promotes sludge formation. This second effect becomes increasingly troublesome as the concentration of ferrous ions in the bath builds up with time. Although it is felt that some iron phosphate is beneficial to the adherence and protective qualities of the coating, excessive amounts are detrimental to corrosion resistance.

A second salt frequently used in phosphating baths is manganese phosphate. The reactions are analogous to those for zinc except that the initial reaction (Eq. 1) yields the secondary as well as tertiary salt.

The coating reaction illustrated above is an extremely slow one, owing largely to cathodic polarization. Accelerating agents are therefore added to the bath to reduce treatment time. Oxidizing agents, such as nitrates, nitrites, or chlorates, behave as depolarizers in oxidizing the hydrogen formed (Eq. 3). Other accelerators for increasing the reaction rate include copper salts, organic compounds such as nitrobenzene, bases such as aniline, toluidene, pyridene, and quinoline. Provided the conditions are so controlled that a fine grain size is obtained, there is no appreciable sacrifice in protective value associated with the use of accelerators. Through the use of accelerators, reaction times have been reduced to less than a minute for paint-base coatings. It has thus become possible to apply phosphate coatings by spray techniques as one step in the conveyor production of large items such as automobile bodies, fenders, etc. The chart in Figure 16-1 summarizes the phosphate treatments in current use together with the basis metals treated and methods and purposes of application.


As in any coating process, the success of the operation depends on proper preparatory surface treatment. Mechanical surface cleaning, such as emery treatment, or blasting with sand, grit, or shot, is employed to remove scale and rust. Degreasing is accomplished with trichlorethylene or in an alkaline bath. Phosphate coatings are particularly sensitive to

<sup>7</sup> Eisler, S. L., and Chamberlain, P. G., *Metal Finishing*, 50, No. 6, 113 (1952).

<sup>8</sup> Phosphoric acid cleaning, as distinguished from a true phosphating treatment, employs a high-acid bath primarily to remove surface dirt and grease, leaving a slight surface etch to promote mechanical bonding with paint, together with a very thin phosphate residue. To insure proper cleaning, the acid concentration must be so high that a substantial crystalline phosphate film cannot be developed.

grease, hence parts should not be handled with bare hands after degreasing.

The protective qualities of phosphate coatings are largely a function of the crystalline character of the film, protection increasing with de-



Courtesy of the Pennsylvania Salt Mfg. Co.

FIGURE 16-1. Summary of types and uses of phosphate coatings.

creasing grain size. In general, refinement of the crystalline structure is obtained with increasing temperature. By using suitable addition agents, the temperature can be reduced with no adverse effect on grain size.<sup>8</sup> Crystal structure is also affected by physical treatment of the surface prior to phosphating. The "wiping" effect, whereby the surface is mechanically wiped prior to treatment, results in refined crystal structure and improved corrosion resistance. This same effect can be approached chemically in a solution containing 1 per cent sodium phosphate and 0.01 per cent titanium as the anhydrous phosphate salt.\* The work is predipped in this solution; then, without rinsing, into the phosphate bath. This treatment is applied to both iron and zinc, but primarily to the latter.

Applying phosphate films to ferrous surfaces is an accepted method of reducing wear and galling on mating parts.<sup>10</sup> Properly lubricated, the coating provides myriads of oil reservoirs, effective in reducing friction. Furthermore, the coating is deformed slightly under pressure, thus reducing maximum applied stress. Heavy phosphate films for this purpose are ordinarily formed from "slow" baths of zinc or manganese phosphate at a temperature between 90 and 100°C (200–210°F).<sup>11</sup> Reaction times range from 10 to 60 minutes, to produce films of 1000 to 4000 mg per sq ft. There is little dimensional change associated with these coatings; it normally is of the order of 0.005 mm (0.0002 inch) for a heavy coating. Of the many applications of this type, many are found in the automotive industry. Piston rings, rocker arms, camshafts, valves, tap-pets, and cylinder liners are frequently phosphated to increase life.

The use of zinc phosphate coatings to reduce friction in wire, tube, and deep drawing applications was suggested about twenty years ago, but was not commercially developed until the recent war. Coatings of 150 to 3000 mg per sq/ft are used, the thicker coatings being specified where deformation is light or moderate. For severe forming operations the thickness is limited to preclude injury to the coating. Lubricated coatings of this nature, by markedly reducing friction, reduce wear on dies, permit faster forming operations, and conserve power.<sup>12</sup> No adverse effects on physical properties result from phosphating. Hardness, tensile strength, and temper are unimpaired.

Although the foregoing friction-reducing uses of phosphate coatings are commercially important, the phosphating treatment is known and

\* Reeves, M., *Metal Ind. (London)*, 78, 7, (1951).

<sup>8</sup> Jernstedt, G., *Trans. Electrochem. Soc.*, 83, 361 (1943).

<sup>10</sup> Rooss, M. B., *Lubrication Eng.*, 6, 117 (1950).

<sup>11</sup> Ayres, R. F., *Materials & Methods*, 34, No. 4, 100 (1951).

<sup>12</sup> Holden, H. A., *Sheet Metal Ind.*, 26, 123, (1949).

Phosphate coatings, being essentially insoluble in most service environments, are protective insofar as they are continuous; continuity, hence, protection, increases with thickness. The corrosion resistance of phosphated but unpainted steel is compared with that of untreated steel in Table 16-1.<sup>14</sup>

TABLE 16-1. CORROSION OF PHOSPHATED STEEL (SAE-1020)  
COMPARED WITH THAT OF UNTREATED STEEL

| Test                  | Untreated (mg/cm <sup>2</sup> ) | Phosphated (mg/cm <sup>2</sup> ) |
|-----------------------|---------------------------------|----------------------------------|
| 744 hours in salt fog | 34.08                           | 3.22                             |
| 1 year rural exposure | 20.39                           | 1.60                             |

The extent to which phosphate coatings aid in the retention of paint on steel panels is shown in Table 16-2.<sup>15</sup>

steel panels is shown in Table 16-2.<sup>10</sup>

In addition to increasing adhesion and retention of paints, phosphate coatings also tend to stifle under film corrosion. A recent six-year test illustrated the protection provided by two spray coats of baked synthetic enamel applied over steel samples treated in three different ways: (1) solvent vapor degreasing, (2) sandblasting, and (3) coating with phosphate. Whereas underfilm and general corrosion were evident on the first

<sup>13</sup> Clarke, S. G., and Longhurst, E. E., *J. Iron Steel Inst. (London)*, 170, 15 (1952).

<sup>14</sup> Darsey, V. M., and Cavanaugh, W. R., Parker Rust Proof Co., *Trans. Electrochem Soc.*, 91, 351 (1947).

<sup>16</sup> Darsey, V. M., Parker Rust Proof Co., "Phosphate Coatings," Reprinted with permission from "Corrosion Handbook," edited by H. H. Uhlig, p. 867, New York, John Wiley & Sons, Inc., 1948.

two surfaces, the phosphate coating improved paint protection and retarded underfilm attack.<sup>15</sup>

The affinity of phosphate coatings for oil and wax is exploited in rust-proofing many articles. The adhesion and abrasion resistance of the coating is such that threaded articles, such as nuts, bolts, and screws, can be

TABLE 16-2. RETENTION OF PAINT BY UNTREATED AND PHOSPHATE-COATED STEEL

|  | Primer Wt. Retained<br>(oz/10 <sup>2</sup> ) | Increase in Retention<br>Over Untreated Steel<br>(%) |
|--|--|--|
| Steel untreated                                | 0.139  | —  |
| Steel-phosphate coated<br>Roller application   | 0.177  | 27.3   |
| Steel-phosphate coated<br>By spray             | 0.200  | 43.9   |
| Steel-phosphate coated<br>By immersion dipping | 0.242  | 74.0   |

so treated. During World Wars I and II small arms were rustproofed by phosphating, then treating with chromic acid and a rust-preventive oil. The corrosion protection obtained is indicated in Table 16-3,<sup>16</sup> in which are listed salt-spray requirements for military equipment finished in this manner.

TABLE 16-3. SALT SPRAY RESISTANCE OF PHOSPHATED STEEL BEFORE AND AFTER OILING

| Class | Coating Wt.<br>(mg/10 <sup>2</sup> ) | Salt Spray Resistance (hours) |       |
|-------|--------------------------------------|-------------------------------|-------|
|       |                                      | Before                        | After |
| A     | 1000-4000                            | 1                             | 24    |
| B     | 1000-4000                            | .2                            | 36    |

Besides iron and steel, other metals, notably zinc and aluminum, are phosphate treated on a large scale. Zinc surfaces which are painted with no intermediate treatment provide inadequate service due primarily to the reaction of zinc with the paint vehicle. Zinc soaps are formed, destroying the bond between the paint and the zinc. Phosphating is one treatment used to avoid this difficulty, and also to increase the mechanical anchorage of the paint. Cadmium is treated in the same way. The baths are of zinc phosphate in which the work is dipped for about 2 minutes, forming a film of 75 to 200 mg per sq ft.<sup>17</sup> Phosphating is recommended frequently for zinc- or cadmium-plated steel that is to be painted. Zinc-flash bonderizing consists in applying a thin electrodeposit of zinc which is given a phosphating treatment, then painted. This composite coating provides a higher degree of corrosion protection to iron or steel than does normal phosphating and painting. The zinc thickness is

<sup>15</sup> Gentieu, N. P., *Machine Design*, 24, No. 2, 141 (1952).

<sup>17</sup> Douty, A., *Plating*, 38, 1031 (1951).

usually 0.0006 to 0.0015 mm (0.000025 to 0.00006 inch) for indoor and 0.0025 to 0.0035 mm (0.00010 to 0.00015 inch) for outdoor exposure.

For treating tin a special technique is available called "Protecta Tin" in which an oxide and phosphate complex are formed on the tin, imparting an increased resistance to corrosion and to staining by sulfur products.<sup>18</sup> Processing is carried out by immersion for less than 30 seconds at 85°C in a solution containing 9 pounds trisodium phosphate (anhydrous), 8 pounds sodium dichromate, 20 pounds sodium hydroxide, 3 pounds wetting agent, and water to make 121 gallons.<sup>19</sup> The treatment does not affect the appearance of the metal nor does it interfere with subsequent lacquering or lithographic printing. This process is used to increase the shelf-life of canned foods both by retarding rusting of the outside of the can during storage in damp conditions, and by preventing the unsightly blackening of can interiors resulting from sulfur originating in meat, fish, soup, and many vegetables.

#### CHROMATE COATINGS

Chromate conversion coatings were widely used during World War II for protection of zinc- and cadmium-plated parts in tropical service. Since that time they have undergone marked commercial development, and are now firmly established in the metal finishing field. They are used purely for protection purposes without additional finishing treatment, or they may be finished with lacquer or paint to combine protection with product appearance. Their use has been extended to the protection of zinc-base die castings and aluminum.

Zinc, when exposed to conditions that give rise to moisture condensation, develops a bulky white corrosion product. This most readily occurs in highly humid conditions such as prevail in the tropics or the Gulf Coast where the daily temperature variation causes intermittent condensation or dew formation. Storage of zinc or zinc-coated parts in unheated warehouses during periods of high humidity or the packaging of such products in boxes made of unseasoned wood or damp paper stock has caused corrosion of this "white bloom" type. In addition to detracting from the appearance of the part, these corrosion products can impair the operation of certain types of equipment, such as relays and switches. It is for such applications that chromate coatings are largely employed to retard the corrosion of zinc and cadmium plated parts and zinc-base die castings.

Applications of chromate coatings are predominantly by immersion

<sup>18</sup> Kerr, R., *J. Soc. Chem. Ind.*, 65, 101 (1946).

<sup>19</sup> *Product Finishing (London)*, 3, No. 12, 58 (1950).

processes, although electrolytic methods are used to some extent in the aircraft industry. The bath compositions are largely proprietary but all contain two basic constituents: hexavalent chromium ions and a mineral acid. Some also contain one or more organic acids. On immersion, the zinc or cadmium article is attacked by the mineral acid with an attendant rise in pH of the solution next to the metal. At the same time some hexavalent chromium is reduced to the trivalent state. At a critical pH the trivalent chromium and some hexavalent chromium are coprecipitated on the metal surface.

One of the oldest and still popular chromating processes is known as the "Cronak"\* process<sup>20</sup> concerning which details have been published.<sup>21</sup> The bath contains chiefly sodium dichromate in fairly high concentrations, slightly acidified with sulfuric acid. Analytical studies indicate the film formed from this bath to be a basic chromium chromate of the general formula  $\text{Cr}_2\text{O}_3 \cdot \text{CrO}_3 \cdot x\text{H}_2\text{O}$ . A typical film, dried at 110°C (230°F), has been analyzed as follows:

|                     |       |
|---------------------|-------|
| Hexavalent chromium | 8.68% |
| Trivalent chromium  | 28.2% |
| Sulfate             | 3.27% |
| Zinc                | 2.12% |
| Sodium              | 0.32% |
| Water               | 19.3% |

← NO PHOSPHATE !!

The thickness is about 0.0005 mm (0.00002 inch).

Chromate films are generally noncrystalline, nonporous, and gel-like. They are quite susceptible to damage from abrasion immediately following film formation; hence should be aged 12 to 24 hours, before being subjected to normal shop handling. Electrolytically applied coatings are not subject to this limitation.

Chromate films which provide maximum protection contain both trivalent and hexavalent chromium.<sup>22</sup> Protection is provided in two ways. The nonporous nature of the film physically excludes, to a large extent, moisture from the metal. At discontinuities in the film, the hexavalent chromium, being slightly soluble, exerts its well-known inhibiting action. Experiments show that the formation of white corrosion product is inhibited so long as a minimum amount of hexavalent chromium remains in the film. The useful life of a chromated part thus depends on the rate at which hexavalent chromium is leached from the film, i.e., on the degree of wetting of the part. The protection provided by a Cronak coating in stagnant water is illustrated in Table 16-4.<sup>21</sup>

\* Registered trade mark of New Jersey Zinc Company.

<sup>20</sup> U.S. Patent 2,035,380 (Mar. 24, 1936) E. J. Wilhelm (to New Jersey Zinc Co.).

<sup>21</sup> Anderson, E. A., *Proc. Am. Electroplaters' Soc.*, 30, 6 (1943).

<sup>22</sup> Ostrander, C. W., *Plating*, 38, 1033 (1951).

## Sodium Dichromate(VI)

8683

**Tetrachloride.** Yellow, somewhat deliquescent crystals. Sol in about 1 part water; slightly in alcohol. The aq soln is alkaline. *Keep well closed.* The tetrachloride is unstable with respect to water content. mp  $> 300^\circ$ .

**<sup>51</sup>Cr-Labelled compound.** [10039-33-9] Sodium chromate-<sup>51</sup>Cr; sodium radio-chromate-<sup>51</sup>Cr; Chromotope Sodium; Rchromate-51. <sup>51</sup>Cr,  $\text{Na}_2\text{Cr}_2\text{O}_7$ . Picked from radioactive chromium (<sup>51</sup>Cr) which has a half-life of 27.7 days. The emission of gamma rays is applicable to biological tags and tracing. Other properties identical to those of unlabeled sodium chromate.

**USE:** Protection of iron against corrosion and rusting.

**THERAP. CAT:** <sup>51</sup>Cr-labeled compound as diagnostic aid (blood volume determination; blood cell survival).

**8675. Sodium Citrate.** (69414-31) Trisodium citrate; Citrusodium; Citrimin; Urisal.  $\text{C}_6\text{H}_5\text{Na}_3\text{O}_7$ ; mol wt 258.07. C 37.02%, H 1.95%, Na 36.73%, O 43.40%. Toxicity data: Gruber, Halbesien, *J. Pharmacol. Exp. Ther.* 94, 65 (1948).

**Dihydrate.** White, odorless crystals, granules or powder; cool, saline taste. Stable in air; becomes anhydrous at  $150^\circ$ . Sol in 1.3 parts water, 0.6 part boiling water. Insol in alcohol. The aq soln is slightly alkaline to litmus, pH about 8. LD<sub>50</sub> i.p. in rat: 6.0 mmol/kg (Gruber, Halbesien).

**Pentahydrate.** Relatively large, colorless crystals or white granules. Not as stable as the dihydrate, drying out on exposure to air and also caking. *Keep well closed.*

**USE:** In photography, as sequestering agent to remove trace metals; *in vitro* anticoagulant; as emulsifier; acidulant and sequesterant in foods.

**THERAP. CAT:** Systemic alkalizer; diuretic; expectorant; sudorific.

**THERAP. CATIVITY:** Anticoagulant for collection of blood.

**8676. Sodium Citrate, Acid.** [144-33-2] Disodium citrate; disodium hydrogen citrate; Alkalitron.  $\text{C}_6\text{H}_6\text{Na}_2\text{O}_7$ ; mol wt 236.09. C 30.53%, H 2.56%, Na 19.48%, O 47.44%.

**Sesquihydrate.** White powder, saline taste. One gram dissolves in slightly less than 2 ml water; pH of a 3% w/v soln in water: 4.9 to 5.2.

**USE:** Anticoagulant, generally in solution with glucose, to prevent the clotting of blood intended for transfusion. Preferable to sodium citrate, since it prevents carmelization of glucose on sterilization because of its acidity. A suitable soln contains 1.7 to 2%, and 2.5% dextrose; 1.20 ml of this soln prevents the clotting of 420 ml blood.

**8677. Sodium Citratelutite.** [13600-98-1] Trisodium butanedinitrate-*N*-acetylbutyl-3-*l*-sodium hexanitrocoabaltate-11.  $\text{C}_{20}\text{H}_{18}\text{N}_{10}\text{Na}_3\text{O}_{21}$ ; mol wt 403.94. C 14.59%, N 20.81%, Na 17.07%, O 47.53%.  $\text{Na}_2\text{CO}_3$  10.

**Yellow to brownish-yellow, crystalline powder.** Very sol in water. Slightly in alc. Due to mineral acids, but unaffected by dil acetic or similar organic acids. The aq soln dries gradually but if a few drops of acetic acid are added it may be kept for about 3 months.

**USE:** For the detection of potassium with which it forms a slightly sol complex.

**8678. Sodium Cyanate.** [917-61-31] Cyanic acid sodium salt.  $\text{CNNaO}$ ; mol wt 65.01. C 18.48%, N 21.53%, Na 35.36%. 11.24.61%. NaOCN. Prep and properties: *Gmelin's Sodium* [Hd. ed.] 21, 799-801 (1928) and supplement, part 4, 1382-1386 (1967). Used experimentally in treatment of sickle cell anemia. Effect: Cyanic on sickling: *May et al., Cancer* 1, 658 (1972); P. N. Gillette *et al.*, *N. Engl. J. Med.* 290, 654 (1974). Pharmacology and toxicology: *Cerami et al., J. Pharmacol. Exp. Ther.* 185, 653 (1971). Clinical studies: Peterson *et al., Ibid.* 186, 577 (1971).

**Colorless needles** from alcohol  $d_4^{20}$  1.803, mp  $551^\circ$ . Sol in water; decomposes in furfuryl  $\text{Na}_2\text{CO}_3$  and urea. Soly in alc (0.1 to 0.2 g/100 g solvent). Insol in ether. LD<sub>50</sub> i.p. in mice: 260 mg/kg (Cerami).

**8679. Sodium Cyanide.** [143-33-9] Cyanogen.  $\text{CNNa}$ ; mol wt 49.01. C 24.71%, N 28.58%, Na 36.91%. NaCN. This cyanide of cyanide is 95-98% pure. Mixtures of sodium cyanide with sodium chloride or carbonate for special uses are also marketed. Toxicity study: *Singh et al., Am. Ind. Hyg. Assoc.* 30, 370 (1969).

**White granules or fused pieces. Violent poison!** Odorless when perfectly dry; somewhat deliquescent in damp air and emits slight odor of HCN, mp  $561^\circ$ . Freely sol in water, slightly in alcohol. The aq soln is strongly alkaline and rapidly decomposes; the soln readily dissolves gold and silver in presence of air. *Keep well closed.* LD<sub>50</sub> orally in rats: 15 mg/kg (Singh).

**Caution:** Potential symptoms of overexposure are irritation of eyes and skin; weakness, headache and confusion; nausea, vomiting; increased rate of respiration; slow gasping respiration; asphyxia; thyroid and blood changes. See *MOSHS Pocket Guide to Chemical Hazards* (DHHS/NIOSH 97-140, 1997) p 323.

**USE:** Extracting gold and silver from ores; electroplating baths; fumigating citrus and other fruit trees, ships, railway cars, warehouses, etc.; unusual hydrocyanic acid and many other cyanides; case hardening of steel.

**8680. Sodium Cyanohydroxide.** (25895-40-7) Sodium (cyano-Citrihydroborate) 1-1; sodium borocyanohydride; sodium cyanohydroborate.  $\text{C}_2\text{H}_2\text{BNNa}$ ; mol wt 62.84. C 10.11%, H 4.81%, B 17.20%, N 22.29%, Na 36.58%. NaBH<sub>4</sub>·CN. Reducing agent prepared from NaBH<sub>4</sub> and HCN. R. C. Wade *et al.*, *Inorg. Chem.* 9, 3146 (1970); R. C. Wade, DE 3028569 corresp. to US 3667923 (1971, 1972 both to Ventron). Review of prep. properties and uses: C. F. Lau, *Synthesis* 1975, 135-146.

**White, hygroscopic powder.** mp  $240-242^\circ$  (dec).  $d_4^{25}$  1.199. Soly (100 g solvent in water  $20^\circ$ ): 212; in THF (25%): 37.2; in diglyme (25%): 17.6. Very sol in methanol; slightly sol in ethanol, isopropylamine; insol in ethyl ether, benzene, hexane. Stable in air to pH 2; undergoes rapid hydrolysis in 12N HCl. Rate of hydrolysis  $10^{-4}$  at pH 1.


**USE:** Selective reducing agent for aldehydes, ketones, oximes, amines; does not reduce amides, ethers, lactones, nitriles, nitro compounds and epoxides. Also used for reductive amination of ketones and aldehydes, reductive alkylation of amines and hydrazines, reductive displacement of halides and tosylates, deoxygenation of aldehydes and ketones. See Lane, *loc. cit.*

**8681. Sodium Diacetate.** [126-56-5] Sodium acid acetate; Pykon.  $\text{CH}_3\text{COONa}(\text{CH}_3\text{COOH})$ . Described as a "broad" sample of sodium acetate and acetic acid.

**White powder.** dec above  $150^\circ$ . Sol in water, attaining 42.25% available acetic acid.

**USE:** Acetic acid in solid form; as an inhibitor of mold and rope-forming bacteria in bread: Glabe, *Food Inds* 14, no. 2, 46 (1942); as sequestrant.

**8682. Sodium Dibromate.** [14992-29-7] 2,6-Nitro-1,4-dimethylphenyl-1-naphthylsulfonate acid sodium salt; L-1633; 1633 Labax. Butanate; Reagent; Dibromate; Keaton; 1-methylsul.  $\text{C}_{14}\text{H}_{10}\text{Br}_2\text{NaO}_6\text{S}$ ; mol wt 342.43. C 33.14%, H 6.77%, N 6.71%, O 14.02%. S 9.36%. Although most sources refer to this compound as sodium 2,6-di-*tert*-butylphenylphthalate sulfonate, it is a mixture of at least two isomers. Prep and separation of isomers: *Manuel et al., Can. J. Chem.* 39, 729 (1961).



**Slightly hygroscopic crystals.** dec  $> 300^\circ$ . Slightly sol in cold water (0.5-1.0 g/100 g solvent) in hot water; sol in methanol, less sol in ethanol. Aq solns are stable to boiling.

**THERAP. CAT:** Antitumor.

**8683. Sodium Dichromate(VI).** [10585-11-9] Sodium bichromate; bichromate of soda.  $\text{Cr}_2\text{Na}_2\text{O}_7$ ; mol wt 261.97. Cr 39.70%, Na 17.53%, O 42.75%.  $\text{Na}_2\text{Cr}_2\text{O}_7$ . Usually prep from  $\text{Na}_2\text{CO}_3$  and  $\text{H}_2\text{SO}_4$ . Description of industrial processes: Möller, *Glassman in Ullmann's Encyclopedia der technischen Chemie*, vol. 5 (Munich, 3rd ed., 1954) p 575; *Falk, Keyer & Clark's Industrial Chemicals*, P. A. Lowenheim, M. K. Moran, Eds. (Wiley-Interscience, New York, 4th ed., 1975) pp 731-736.



$ZnI_2$ , m. 132-3°;  $(Et_4S)_2ZnI_2$ , m. 149°;  $(Et_4MeS)_2ZnI_2$ , m. 173-4°;  $(Et_4PrS)_2ZnI_2$ , m. 145°. ALFRED HOFFMAN

Composition of complex metal cyanide radicals. Complex Ni cyanide radical (MASAKI) 2. Synthesis and x-ray investigation of  $NiCr_2O_4$  (HOLGERSSON) 2.

LAFUMA, HENRI: Recherches sur les aluminates de calcium et sur leurs combinaisons avec le chlorure et le sulfate de calcium. Paris: Vuibert. 68 pp. P. 16.

## 7—ANALYTICAL CHEMISTRY

W. T. HALL

An improved method of quantitative spectrographic analysis. C. C. NITCHIE AND G. W. STANDEN. *Ind. Eng. Chem., Anal. Ed.* 4, 182-85(1932).—The method employed is a modification of the methods of Gerlach and Schweitzer and N. (C. A. 23, 1587). In the improved method an addnl. element is added to the sample in a const. known amt. for comparison purposes. The use of a recording microphotometer is now justified and considerable time is saved. Four requirements are listed for satisfactory comparison of spectral lines. App. and procedure are described, and spectra and microphotometric records are shown. Concrete examples are given and the errors are analyzed. The deviation from the mean of 4 detns. is 1 part in from 10 to 20. H. A. S.

Micro-alkalimetry and acidimetry. S. K. CHIRKOV. *Bull. inst. recherches biol. Perm* 7, No. 7/8, 427-40(German summary) 440-1(1931).—The soln. to be investigated is titrated to the intermediate color of a 2-color indicator, with not stronger than 0.01 *N* reagents from a membrane microburet. Formulas are given for calcg. the decrease in acidity or alkali.  $pH$  values are taken from tables. R. H. FERGUSON

Thermometric titration. TAKAYUKI SOMIYA. *J. Soc. Chem. Ind.* 51, 135-40T (1932); cf. C. A. 21, 1425, 3030; 23, 1840, 2907, 4907, 4908; 24, 3389, 3915.—The necessary app. is shown and numerous applications of the method are described.

W. T. H.

Use of benzidine acetate as indicator in molybdo-manganimetry; application to the electrolytic determination of a few hundredths of a milligram of copper. R. GUILLEMET AND L. THIVOLLE. *Compt. rend. soc. biol.* 108, 30-2(1931).—Fontès and Thivolle (C. A. 17, 1199) developed a method for detg. Cu which depended upon the fact that when Cu is plunged into a phosphomolybdate reagent (boil 40 g. of  $NH_4$  molybdate, 60 cc. of NaOH soln., d. 1.36, and 100 cc. of water until no more  $NH_3$  is evolved, cool, add 200 cc. of water and 200 cc. of  $H_3PO_4$ , d. 1.30, boil 15 min., cool and dil. to 1 l.) the Cu dissolves, forming a blue soln. which becomes colorless when titrated with  $KMnO_4$ . To overcome the difficulty in detg. the end point, it is now recommended to use benzidine acetate soln. as indicator. Dissolve 1 g. of benzidine in 10 cc. of glacial AcOH, boil and dil. to 100 cc. After washing an electrolytic Cu deposit, plunge the electrode into enough of the phosphomolybdic reagent to cover it (3 cc. in a small tube with a Pt wire cathode), allow the color to develop for a few min., while using the cathode as a stirrer and titrate with dil.  $KMnO_4$  after adding the indicator. W. T. H.

A neutral buffered standard, for hydrogen-ion work and accurate titrations, which can be prepared in one minute. ROGER J. WILLIAMS and CARL M. LYMAN. *J. Am. Chem. Soc.* 54, 1911-2(1932).— $NH_4OAc$  solns. through wide limits of concn. have a  $pH$  of almost exactly 7.00. W. T. H.

New reagent for the detection of hydroxy acids. C. H. LIBERALLI. *Bol. assoc. brasil. pharm.* 12, No. 10, 24(1931).—Hydroxy acids can be detected by the use of the following reagent:  $FeCl_3$  (10%) 32.4 cc.,  $KCNs$  (10%) 68.2 cc.,  $H_2O$  to 100 cc. The reagent turns yellow on the addn. of a neutral soln. of hydroxy acid. AcOH and oxalic acid also give the same color. Addn. of 1 drop of  $HNO_3$  brings back the original red color with hydroxy acids. With AcOH and oxalic acids the color does not return. R. S. G. B.

Preparation of sodium cobaltinitrite as potassium reagent. E. RUPP AND A. POGGIANDONI. *Apoth. Ztg.* 47, 282-3(1932).—To 5 g. of powd.  $Co(NO_3)_2$  in 2 l. AcOH and 1 g.  $H_2O$  add a luke-warm soln. of 10 g.  $NaNO_2$  in 1 l.  $H_2O$ , remove the  $Na_2O$  by a 30-min. current of aspirated air through the mixt., allow to stand 15-30 min., pass through a filter to remove any turbidity and mix in a porcelain mortar with 20 g. of pure, freshly dehydrated  $Na_2SO_4$ , then place in a vacuum desiccator for a day. Triturate the golden yellow cryst. mass and preserve in amber glass. W. O. E.

exchanged at once.  $\text{Fe}^{2+}$  and  $\text{FeY}^-$ , both 0.0125  $M$ , at pH from 1.5 to 5.0 showed an immediate partial and very slow subsequent exchange. Temp. = 25°. Tracers were  $\text{Co}^{57}$ ,  $\text{Fe}^{54}$ , and  $\text{Ni}^{63}$ . Cf. C.A. 42, 15232c. P. E. B.

New approaches to the study of the reaction between potassium and cobaltinitrite ions. Angel del Campo, Vicente Boissier, and Angel Hoyos (Univ. Madrid). *Rev. real acad. cienc. exact., fis. y nat. Madrid* 34, 352-390 (1940).  $\text{K}_2\text{Co}(\text{NO}_2)_6$  was prepared by stirring with DeKoninck's reagent (C.A. 3, 1928; (1909)) to a known soln. of KCl, filtering, drying in a current of air at 100°, and weighing in a tared filter crucible. The wt. of ppt. is less when the soln. is stirred during pptn.; hence adsorption takes place. On long standing, with the ppt. in contact with an excess of  $\text{Na}_2\text{C}_2\text{O}_4(\text{NO}_2)_4$ , the ppt. increases considerably; Na probably substitutes for K in the ppt., as evidenced by qual. analysis. The ppt. is probably a mixt. of  $\text{K}_2[\text{Co}(\text{NO}_2)_6]$ ,  $\text{H}_2\text{O}$  and  $\text{K}_2\text{Na}[\text{Co}(\text{NO}_2)_6]$ , but the K is nevertheless pptd. quant. K, pptd. with  $\text{Li}_2[\text{Co}(\text{NO}_2)_6]$ , can be filtered and washed more easily than when pptd. with the Na reagent, and comes down as well-formed cubic crystals corresponding closely to the formula  $\text{K}_2[\text{Co}(\text{NO}_2)_6]$  when an excess of reagent is employed; the wt. of the ppt. is almost independent of whether or not the soln. is agitated during pptn., in contrast to the large changes observed with the Na reagent. The anion of the K soln. has no effect.

Chemistry of thorium in aqueous solutions. I. Organic and inorganic complexes. R. A. Day, Jr., and R. W. Stoughton (Oak Ridge Natl. Lab., Oak Ridge, Tenn.). *J. Am. Chem. Soc.* 72, 5992-7 (1950).—Equil. const. for the formation of complex ions of Th with the anions of  $\text{HF}$ ,  $\text{HClO}_4$ ,  $\text{Cl}_2\text{CCOOH}$ ,  $\text{HBrO}_3$ ,  $\text{Cl}_2\text{CHCOOH}$ ,  $\text{HNO}_3$ ,  $\text{HCl}$ , and  $\text{ClCH}_2\text{COOH}$  in aq. soln. with a H-ion concn. of 0.5  $M$  and an ionic strength of 0.5 were obtained by detg. the distribution ratios between the aq. soln. and benzene contg. thienyl-trifluoroacetone (I) as a chelating agent. The const. for the 1:1 complexes decrease in the order of the above listing, going from  $4.3 \times 10^4$  for  $\text{Th}^{4+}$  to 1.33. Higher complexing corresponding to Th/anion ratios of 2 and 3 was

found for the first five anions in the list; the corresponding const. are presented. Evidence was found for the existence of double complexes of the type  $\text{Th}(\text{NO}_3)_2\text{F}^{2+}$  and  $\text{Th}(\text{NO}_3)_2\text{F}^{2+}$  in mixts. of  $\text{HNO}_3$  and  $\text{HF}$ . Acetic acid in the aq. phase increases the extractability of the chelated product formed between Th and (I). J. Van Wazer

Sequestering properties of salicylic acid. Complexes of salicylic acid. Giovanni Maunoli, *Ann. chim. (pt. fisica)* 38, 594-601 (1948).—Fe is sepd. from Ti by treating a soln. of the sulfates with  $\text{NH}_4$  salicylate (I) and  $(\text{NH}_4)_2\text{CO}_3$ , followed by pptn. of Fe with  $\text{H}_2\text{S}$ . Addn. of aq.  $\text{NH}_3$  and boiling then gives  $\text{TiO}_2$ . Re is sepd. from Mn, with I, the Mn being pptd. as phosphate, and similarly Fe from Ti, the Ti being pptd. as chromate in presence of I. Na salicylate and  $\text{Be}(\text{OH})_2$  give  $\text{Na}_2\text{Be}_2\text{salicylate}$ ,  $\text{C}_6\text{H}_5\text{O}_2\text{NaBe}$ ; similarly are formed  $\text{Na}_2\text{UO}_2\text{salicylate}$ ,  $\text{C}_6\text{H}_5\text{O}_2\text{Na}_2\text{U}$  ( $+4\text{H}_2\text{O}$ ), and  $\text{K}_4\text{Na}_2\text{salicylate}$ ,  $\text{C}_6\text{H}_5\text{O}_2\text{Na}_2\text{K}$ . B. A.

Electrochemical study of complexes of the silver ion and amino dicarboxylic acids. Suzanne Valladas-Dubois, *Compt. rend.* 231, 1299-1300 (1950).—Aspartic acid and glutamic acid, like glycine, at high pH form complex anions of about the same stability, corresponding to 2 mols. of the amino acid to one of  $\text{AgNO}_3$ . Earl S. McColey

Arsenates—oxidation of arsenious acid (Takahashi) 4. Kinetics and mechanism of solid-phase reactions—in oxide films on pure Fe (Gulbransen) 2. Heavy-metal aluminates (Rüthenberg) 9.

Taurins, A.: Neorganiska Kimija. Württemberg: A. Brokna, A.: Neorganiska Kimija. 1948. 126 pp.

Wells, A. F.: Structural Inorganic Chemistry. New York: Oxford Univ. Press. 1951. 590 pp. \$7.

Experimentelle Einführung in die Anorganische Chemie. Edited by W. Klemm and W. Fischer. Berlin: W. de Gruyter. 1949. 204 pp. DM 7.80. Reviewed in *Angew. Chem.* 63, 55 (1951).

## 7—ANALYTICAL CHEMISTRY

W. T. HALL

History of analytical chemistry in Russia. K. B. Yatsimirskii. *Uspehi Khim.* 18, 622-9 (1949).

Recent developments in inorganic analytical chemistry. J. C. Geertman. *S. African Ind. Chemist* 2, 31-3 (1948).—A description is given of (1) the use of the Walden Ag reductor and internal indicators in the detn. of Fe with  $\text{K}_2\text{Cr}_2\text{O}_7$  (2) detn. of C in presence of large amts. of S, e.g., coal in pyrites concentrates, with  $\text{MnO}_2$  on pumice granules to absorb the  $\text{SO}_2$  and  $\text{SO}_3$ , and (3) detn. of  $\text{CO}_3^{2-}$  in solid materials. B. A.

Analytical methods for determining the concentration of ionically active substances. H. Schwerdtner (Chemnitz, Ger.). *Chem. Tech. (Berlin)* 2, 361-4 (1950).—review.

Qualitative analysis without hydrogen sulfide. X. Reduction method. Toshiyasu Kiba (Kanazawa Univ.). *J. Chem. Soc. Japan, Pure Chem. Sect.* 70, 145-7 (1949); cf. C.A. 45, 2813c.—Metallic Zn can be used as a group reductor to sep. ions from acidic soln. Systematic procedures of group sepn. and identification of ions are given in tables. K. Yamasaki

Fluorometric analysis with morin. E. V. Rouir and H. Dietz (Atelier construct. elec. Charleroi, Charleroi, Belg.). *Congr. groupement avance. meth. anal. spectrograph. produits med.* 12, 149-56 (1949).—Al reacts with morin to produce a fluorescent complex served as a means of detg. 0.001-0.9% Al in bronzes and brasses. For less than 1% Al the relative error was between  $\pm 5$  and  $\pm 7.5\%$ ; for higher percentages,  $\pm 2\%$ . Other metals causing interference in the analysis were removed by electrolysis. M. A. R.

Quantitative analysis of powders by infrared spectrophotometry. Georges Eliot. *Bull. Soc. chim. (Paris)* 1950, 10, 100-1 (1950); cf. C.A. 43, 7366a.—The compensated extinction coeff. method, detd. with an internal standard, is applied to the analysis of powders when Beer's law does not hold, and when there is overlapping between the absorptions of the components of the mixt. Results are given for the analysis of mixts. of cinchonidine, cinchonine,

quinidine and quinine; and of leucine, norleucine, and isoleucine. H. N. Dyer

Spectrochemical analysis of a solution on graphite. M. van Doorselaer, J. Beckhout, and J. Gillis (Univ. Ghent, Belg.). *Congr. groupement avance. meth. anal. spectrograph. produits med.* 12, 51-7 (1949).—Factors which affected bronze analysis according to the method of Rivas (cf. C.A. 32, 1501) were studied. When adsorption of the soln. on graphite took place at a temp. above 100°, the sensitivity of spectral lines was at a max. and their relative intensities were const. An increase in the concn. of the soln. gave a greater sensitivity, except in the case of some elements, as Al, but did not influence the relative intensities. The effect of the vol. of the soln. on the electrode was negligible. A change in the anion ratio of a soln. produced changes in the spectra because of differences in the volatility, as well as adsorption and absorption characteristics of various salts and their complexes. The presence of colloidal Sn gave abnormally high results. M. A. Rinehart

Amperometric titration of sulphydryl groups: microgram analysis. Sheldon Rosenberg, J. C. Perrone, and Paul L. Kirk (Univ. of California Med. School, Berkeley). *Anal. Chem.* 22, 1189-7 (1950).—The argentometric procedure of Kolthoff and Harris (C.A. 44, 78a) is modified. A vibrating Pt electrode is used as a combustion electrode-stirrer, and the titrating soln. is added from a horizontal microburet. For  $\gamma$  amts. of cysteine-HCl and glutathione the error was less than 5% in all cases. Titration of denatured bovine serum albumin should approx. 0.3% sulphydryl (as cysteine); this value was essentially independent of the nature of the denaturing agent. T. H. Dunkelberger

Utilization of ion exchangers in analytical chemistry. XVI. Gunnar Gabrielson and Olof Samuelsson (Chalmers Tekn. Högskola, Göteborg, Sweden). *Swensh Kem. Tid.* 62, 214-20 (1950) (in English); cf. C.A. 44, 6759f.—Aldehydes may be retained quantitatively by an ion exchanger in the bisulfite form. The break-through curves have the same shape as those obtained for inorg. acids, showing that the

# Inorganic Syntheses

"

## Volume II

EDITOR-IN-CHIEF

W. CONARD FERNELIUS

*Syracuse University*

ASSOCIATE EDITORS

LUDWIG F. AUDRIETH

*University of Illinois*

JOHN C. BAILAR, JR.

*University of Illinois*

HAROLD S. BOOTH

*Western Eastern University*

WARREN C. JOHNSON

*University of Chicago*

RAYMOND E. KIRK

*The Polytechnic Institute of Brooklyn*

WALTER C. SCHUMB

*Massachusetts Institute of Technology*

CONSULTANT ON NOMENCLATURE AND INDEXING

JANET D. SCOTT

*The Interchemical Encyclopedia, Inc., Brooklyn*

*First Edition  
Third Impression*

*New York*

McGraw-Hill Book Company, Inc.

*London*

1946

UNIVERSITY OF DAYTON  
DAYTON, OHIO  
REF A3V

The precipitate is finally washed with 12-l. portions of water, centrifuged, and dried at 110° in an electric oven. A yield of 35 g. of the hydrous  $\beta$ -1-hydrate is obtained from 100 g. of  $\text{FeCl}_3 \cdot 6\text{H}_2\text{O}$ . The process of settling in the later stages is very slow and much time may be saved by the use of a centrifuge.

#### Analysis

The amount of chloride in the sample is determined by dissolving a weighed portion in warm, concentrated nitric acid. After evaporation to remove excess acid and dilution with water, the chloride is precipitated as silver chloride, dissolved in ammonia, reprecipitated with dilute nitric acid, and weighed in the usual manner. The iron(III) in the combined filtrates is determined by precipitating with ammonia and is weighed as  $\text{Fe}_2\text{O}_3$  according to the standard procedure. Typical analytical results give an Fe:Cl ratio of 40:1.

#### References

1. BAUDSCH and HARTUNG: *INORGANIC SYNTHESSES*, 1, 135 (1939).
2. WEISER and MULLIGAN: *J. Am. Chem. Soc.*, 87, 238 (1935).
3. WEISER and MULLIGAN: *Chem. Revs.*, 25, 1 (1939).

### 69. HEXAMMINECOBALT(III) SALTS\*

SUBMITTED BY JANNIK BJERRUM† and JAMES P. McREYNOLDS‡  
CHECKED BY ALFRED L. ØVREGAARD§ and R. W. PARRY§

Hexamminecobalt(III) salts may be prepared by any of three methods that depend on oxidation of cobalt(II) ion

\* Procedures for preparing most of these salts were originally submitted by Dr. McReynolds, who was impressed by the simplicity of Dr. Bjerrum's method. Shortly after the manuscript for Vol. II had been sent to the publisher, similar procedures for three of these salts were submitted by Dr. Bjerrum. Inasmuch as the method was developed by Dr. Bjerrum and war conditions prevented his submitting the procedures at an earlier date, the editors have taken the liberty of combining the two sets of directions and presenting them as a joint effort of the two men.

† University of Copenhagen, Copenhagen, Denmark.

‡ The Ohio State University, Columbus, Ohio; deceased.


§ University of Illinois, Urbana, Ill.

in ammoniacal solution: (1) air oxidation, with formation of the pentammine ion, which is converted to the hexammine by heating with aqueous ammonia under pressure;<sup>1,2,4,11</sup> (2) oxidation with an agent such as hydrogen peroxide,<sup>4</sup> iodine,<sup>5</sup> potassium permanganate,<sup>6</sup> lead dioxide,<sup>7</sup> or hypochlorite solutions;<sup>8</sup> (3) oxidation in the presence of a catalyst that allows equilibrium between the pentammine and hexammine ions to be established at room temperature and atmospheric pressure. These compounds may also be prepared indirectly from other hexamminecobalt(III) salts.<sup>1,10</sup>

In the best of the catalytic methods diamminesilver ion<sup>12,13</sup> or decolorizing charcoal<sup>14</sup> is used as a catalyst. The method devised by J. Bjerrum<sup>14</sup> in which decolorizing charcoal is the catalyst is simple, gives high yields of pure product, and is not time-consuming. A high concentration of ammonium salt is sufficient to stabilize the hexamminecobalt(III) ion, and the carbon serves only to establish the equilibrium. Air is used as oxidant except when the cobalt(II) compound is slightly soluble in the ammoniacal solution, as in the preparation of  $[\text{Co}(\text{NH}_3)_6]\text{Br}_3$ , for which hydrogen peroxide is preferable.

#### Procedure

##### A. HEXAMMINECOBALT(III) CHLORIDE



Two hundred and forty grams (1 mol) of cobalt(II) chloride 6-hydrate and 160 g. (3 mols) of ammonium chloride are added to 200 ml. of water. The mixture is shaken until most of the salts are dissolved. Then 4 g. of activated decolorizing charcoal\* and 500 ml. of concentrated ammonia are added. Air is bubbled vigorously

\* In order to obtain a rapid reaction, care must be exercised in the choice of this catalyst. Charcoal from the center of a package has been found to be much more effective than that from the top.

through the mixture until the red solution becomes yellowish brown (usually about 4 hr.).\* The air inlet tube is of fairly large bore (10 mm.) to prevent clogging with the precipitated hexaminecobalt(III) salt.

The crystals and carbon are filtered on a Büchner funnel and then added to a solution of 15 to 30 ml. of concentrated hydrochloric acid in 1500 ml. of water; sufficient acid should be used to give the entire mixture an acid reaction. The mixture is heated on a hot plate to effect complete solution and is filtered hot. The hexaminecobalt(III) chloride is precipitated by adding 400 ml. of concentrated hydrochloric acid and slowly cooling to 0°. The precipitate is filtered, washed first with 60 per cent and then with 95 per cent alcohol, and dried at 80 to 100°.† Yield 230 g. (85 per cent). *Anal.* Calcd. for  $[\text{Co}(\text{NH}_3)_6]\text{Cl}_2$ : Co, 22.0; Cl, 39.8;  $\text{NH}_3$ , 38.2. Found: Co, 22.0; Cl, 39.8;  $\text{NH}_3$ , 38.1.

#### B. HEXAMINECOBALT(III) NITRATE

1.  $4\text{Co}(\text{NO}_3)_2 + 4\text{NH}_4\text{NO}_3 + 20\text{NH}_3 + \text{O}_2 \rightarrow 4[\text{Co}(\text{NH}_3)_6](\text{NO}_3)_3 + 2\text{H}_2\text{O}$
2.  $[\text{Co}(\text{NH}_3)_6]\text{Cl}_2 + 3\text{HNO}_3 \rightarrow [\text{Co}(\text{NH}_3)_6](\text{NO}_3)_3 + 3\text{HCl}$

**Method 1.** Seventy-three grams of cobalt nitrate hydrate (0.25 mol) is dissolved in 100 ml. of water, and, in the order mentioned, 80 g. (1 mol) of ammonium nitrate, 2 g. of activated charcoal, and 180 ml. of concentrated ammonia (about 2.5 mols of  $\text{NH}_3$ ) are added. The solution is oxidized by air as specified in Procedure A. The salt is washed with a little ice-cold water and is dissolved on a steam bath in 1300 to 1500 ml. of water containing enough nitric acid to give the mixture an acid reaction. After


\* Care should be taken that the bubbling is not too vigorous, as this removes part of the ammonia from the solution. If this happens, the solution turns red instead of becoming yellow. Although more ammonia may be added, the yield will be decreased somewhat.

† When the salt is dried at a higher temperature, it sometimes turns green. The original color is restored by redissolving and reprecipitating with hydrochloric acid.

removal of the carbon by filtration, the solution is treated with 200 ml. of concentrated nitric acid and left to cool. The precipitated salt is washed with water and alcohol and dried at 100°. Yield 77 to 79 g. (88 to 90 per cent). *Anal.* Calcd. for  $[\text{Co}(\text{NH}_3)_6](\text{NO}_3)_3$ : Co, 17.0;  $\text{NH}_3$ , 29.4. Found: Co, 16.9;  $\text{NH}_3$ , 29.4.

**Method 2.** The precipitate from the oxidation of cobalt(II) chloride (Procedure A) is dissolved in 1500 ml. of water containing 15 to 30 ml. of concentrated nitric acid. The carbon is removed and the salt precipitated with 450 ml. of concentrated nitric acid. The crystals are washed with two 200-ml. portions of alcohol to remove excess acid and dried at 100°. Yield 103 g. (88 per cent). A solution of these crystals gives only a slight turbidity with silver nitrate.

#### C. HEXAMINECOBALT(III) BROMIDE



Twenty-four grams (0.20 mol) of cobalt carbonate\* is added slowly to 100 ml. of 45 per cent hydrobromic acid (0.80 mol). To the solution, 2 g. of activated charcoal and 120 ml. of concentrated ammonia (1.6 mols of  $\text{NH}_3$ ) are added. The precipitate of cobalt(II) salt that appears is disregarded, and 40 ml. of 30 per cent hydrogen peroxide (0.40 mol) is added slowly while the solution is stirred. When the vigorous effervescence has ceased, the main part of the cobalt(II) precipitate has been converted into the desired product. To complete the equilibrium adjustment, the mixture is heated for 5 min. on a steam bath and then left standing for  $\frac{1}{2}$  hr. The salt-carbon mixture is filtered, washed with a little cold water, and treated with 900 to 1000 ml. of water containing sufficient

\* A cobalt determination must be made on the cobalt carbonate used if an accurate check on the yield of the complex salt is desired.

# Inorganic Syntheses

## Volume IV

### EDITOR-IN-CHIEF

JOHN C. BAILAR, JR.  
*University of Illinois*

### ASSOCIATE EDITORS

JACOB KLEINBERG  
*University of Kansas*

THERALD MOELLER  
*University of Illinois*

EUGENE G. ROCHOW  
*Harvard University*

WALTER C. SCHUMB  
*Massachusetts Institute of Technology*

JANET D. SCOTT  
*The Interscience Encyclopedia, Inc.*

RALPH C. YOUNG  
*Massachusetts Institute of Technology*

### ADVISORY BOARD

LUDWIG F. AUDRIETH  
*University of Illinois*

ARTHUR A. BLANCHARD  
*Massachusetts Institute of Technology*

W. CONARD FERNELIUS  
*The Pennsylvania State College*

W. C. JOHNSON  
*University of Chicago*


RAYMOND E. KIRK  
*The Polytechnic Institute of Brooklyn*

H. I. SCHLESINGER  
*University of Chicago*

New York    Toronto    London  
McGRAW-HILL BOOK COMPANY, INC.  
1953


grinding procedure is repeated. The residue is again collected on a filter and washed with cold water until the filtrate is no longer orange, but instead is faintly greenish. The salt is finally washed with methanol and ether and dried at 50°. Yield, 7.8 g. (86%). *Anal.* Calcd. for  $[\text{Co}(\text{NH}_3)_5\text{I}](\text{NO}_3)_2$ :  $\text{NH}_3$ , 21.8. Found:  $\text{NH}_3$ , 21.8.

#### D. NITROPENTAMMINECOBALT(III) NITRATE<sup>4</sup>



Ten grams of carbonatopentamminecobalt(III) nitrate (0.036 mol) is suspended in 25 ml. of water, and 10 g. of sodium nitrite (0.14 mol) and 10 ml. of colorless nitric acid (1:1 concentrated acid and water) are added. The mixture is stirred for 15 minutes at room temperature, and then 200 ml. of methanol is added to the slurry. The precipitate is collected on a filter, washed with methanol and ether, and dried at 50°. Yield, 10 g. (88%). *Anal.* Calcd. for  $[\text{Co}(\text{NH}_3)_5\text{NO}_2](\text{NO}_3)_2$ :  $\text{NH}_3$ , 27.1. Found:  $\text{NH}_3$ , 27.1.

#### E. NITRATOPENTAMMINECOBALT(III) NITRATE<sup>5</sup>



Ten grams of carbonatopentamminecobalt(III) nitrate (0.036 mol) is suspended in 25 ml. of water, and 20 ml. of colorless nitric acid (1:1 concentrated acid and water) is added with stirring. When the evolution of carbon dioxide has stopped (10 minutes), 100 ml. of methanol is added, the aquopentammine cobalt(III) nitrate is collected on a filter, and washed with alcohol and ether. This salt is heated at 100° for 18 hours (until 1 mol of water is lost), yielding 10 g. (83%) of the desired material. *Anal.* Calcd. for  $[\text{Co}(\text{NH}_3)_5\text{NO}_3](\text{NO}_3)_2$ :  $\text{NH}_3$ , 25.8. Found:  $\text{NH}_3$ , 25.6.

# Inorganic Syntheses

VOLUME VI

## EDITOR-IN-CHIEF

EUGENE G. ROCHOW

*Harvard University*

## ASSOCIATE EDITORS

EUGENE O. BRIMM  
*Linde Company*

JOSEPH J. KATZ  
*Argonne National Laboratory*

GEORGE H. CADY  
*University of Washington*

JACOB KLEINBERG  
*University of Kansas*

HENRY F. HOLTZCLAW, JR.  
*University of Nebraska*

JANET D. SCOTT  
*G. & C. Merriam Company*

GEOFFREY WILKINSON

*Imperial College of Science & Technology*

## ADVISORY BOARD

LUDWIG F. AUDRIETH  
*University of Illinois*

THERALD MOELLER  
*University of Illinois*

JOHN C. BAILAR, JR.  
*University of Illinois*

HERMAN I. SCHLESINGER  
*University of Chicago*

W. CONARD FERNELIUS  
*The Pennsylvania State University*

WALTER C. SCHUMB  
*Massachusetts Institute of Technology*

WARREN C. JOHNSON  
*University of Chicago*

RALPH C. YOUNG  
*Massachusetts Institute of Technology*

McGRAW-HILL BOOK COMPANY, INC.

New York    Toronto    London

1960



safety trap and into a beaker of water where the acid is titrated with 2 *N* sodium hydroxide solution.


The mixture is stirred at a rapid rate and heated for 30 minutes to 126°, whereupon the black slurry thickens. Only approximately 1 ml. of the sodium hydroxide is consumed in this initial heating. The reaction is then allowed to proceed rapidly at 128 to 139° for 2 hours. In the course of the reaction the mixture becomes light tan and appreciably less viscous, and the theoretical amount of sodium hydroxide is required to neutralize the hydrogen chloride which is evolved. Very little additional hydrogen chloride is liberated during another hour of heating.

The solid is filtered, washed repeatedly with chloroform or benzene, and dried *in vacuo*; the yield is 99%. *Anal.* Calcd. for  $\text{FeCl}_2$ : Fe, 44.06. Found: Fe, 43.89.

#### References

1. P. KOVACIC and N. O. BRACE: *J. Am. Chem. Soc.*, **76**, 5491 (1954).
2. N. O. BRACE: U.S. patent 2,719,074 (1955).

### 55. CARBONATOTETRAMMINECOBALT(III) NITRATE



SUBMITTED BY G. SCHLESSINGER\*

CHECKED BY JOHN W. SIMMONS,† GERHARDT JABS,† AND MARK M. CHAMBERLAIN†

The first salts of this series were prepared by Vortmann<sup>1</sup> and later extensively investigated by Jørgensen,<sup>2</sup> who, however, gave only semiquantitative synthetic preparations.

\* University of Pennsylvania, Philadelphia, Pa.

† Western Reserve University, Cleveland, Ohio.

The method given below, which is a more exact procedure than given hitherto (and which may be significantly shortened by the use of hydrogen peroxide instead of air as oxidizing agent) may also be used, virtually without change, for the preparation of the chloride, bromide, iodide, sulfate, selenate, and oxalate of the carbonatotetrammine series simply by using an equivalent amount of the corresponding cobalt(II) salt as starting material.

### Procedure

One hundred grams of cobalt(II) nitrate 6-hydrate (0.344 mol) is dissolved in 100 ml. of warm water and added to a mixture of 200 g. of ammonium carbonate (2.08 mols) in 1 l. of water and 500 ml. of concentrated ammonia. The resulting liquid is oxidized by sucking air through the solution contained in two 1-l. suction flasks fitted with stoppers and glass air-inlet tubes reaching almost to the bottoms of the vessels.\* After  $2\frac{1}{2}$  hours, when the oxidation is complete, the solution is evaporated on the steam bath to a volume of 500 ml. Any cobalt(III) oxide is filtered off while hot, and further evaporation to 350 ml. is carried out. During the course of the evaporation 50 g. of solid ammonium carbonate should be added in 5-g. portions at regular intervals.† The solution is next cooled in ice, filtered by suction, and the crystals pressed well dry. The crystals may be washed with 75 ml. of alcohol. The filtrate is evaporated down to 100 ml., with the addition of four 5-g. portions of ammonium carbonate, and more product is isolated as above. The first batch of product, 48 to 50 g., is analytically pure, but the second may be contaminated with a trace of carbonatopentamminecobalt(III) nitrate, which is

\* A timesaving but more costly method of oxidation is to add 250 ml. of 3% hydrogen peroxide slowly to the well-stirred cobalt(II) ammine mixture. After standing 10 minutes the solution is evaporated as below. The yield is the same.

† The regular addition of the ammonium carbonate is emphasized.

the unsym. compd. reacts more slowly. The trisulfonates hydrolyze rapidly, giving  $\text{SO}_3^-$ ,  $\text{SO}_3^-$ ,  $\text{SO}_3^-$ , and a little tetrasulfonate, azedisulfonate is an intermediate. Tetrasulfonate hydrolyzes only slightly. R. H. Jaquith

The stability of metal tetraethylenepentamine complexes. a Charles N. Reilley and J. H. Holloway (Univ. of N. Carolina, Chapel Hill). *J. Am. Chem. Soc.* 80, 2917-19 (1958).—From potential-pH diagrams the stability constants (pK) of the following metal complexes of tetraethylenepentamine (I) were detd.:  $\text{Hg(II)}$ , 27.7;  $\text{Cu(II)}$ , 22.9;  $\text{Ni(II)}$ , 17.8;  $\text{Zn}$ , 15.4;  $\text{Cd}$ , 14.0;  $\text{Pb(II)}$ , 10-11;  $\text{Mn(II)}$ , 7.0;  $\text{Bi(III)}$ ,  $\text{Ca}$ ,  $\text{Mg}$ ,  $\text{Sr}$ ,  $\text{Ba}$ ,  $\text{Al}$ , and  $\text{La}$ , all negligible. pK values of 2-6 for I were found to be 4.1, 8.2, 9.2, and 10.0, resp., at 25° and with an ionic strength of 0.10. Analytical applications for I complexes are discussed. b

Arsenic(III) oxychloride, a new type of polymer bond. E. Thilo and P. Flögel (Akad. Wissenschaften, Berlin-Adlershof). *Angew. Chem.* 69, 754 (1957) (in German).— $\text{As}_2\text{O}_3$  dissolves in  $\text{AsCl}_3$  with formation of an amorphous, hard polymer which has the structure  $\text{ClAsO(OC(AsO)}_n\text{AsO)}_n\text{Cl}$ .

Rudolph J. Marcus The synthesis of metal complexes. III. Synthesis of ethylenediaminecarbonate, and ethylenediamineoxalato series of cobalt(III) complexes. Motochichi Mori, Maruji Shibata, Eishin Kyuno, and Koji Hoshiyama (Univ. Kanazawa). *Bull. Chem. Soc. Japan* 31, 291-5 (1958); cf. C.A. 51, 5618h.—Three series of Co(III) complexes were systematically synthesized from the green soln. of potassium trisoxalato cobaltate(III) (I), by means of successive substitution of carbonate by other groups: blue  $\text{K[Co(en)(CO}_3)_2\text{]}\cdot\text{H}_2\text{O}$  (II); violet  $\text{K[Co(en)(CO}_3)_2\text{]}\cdot\text{H}_2\text{O}$  (III);  $\text{[Co(en)(CO}_3)_2\text{Cl]}\cdot\text{H}_2\text{O}$  (IV);  $\text{[Co(en)Cl}_2\text{]}\cdot\text{3H}_2\text{O}$  (V); blue- $\text{K[Co(NH}_3)_4\text{(C}_2\text{O}_4)_2\text{]}\cdot\text{H}_2\text{O}$  (VI); violet- $\text{K[Co(NH}_3)_4\text{(C}_2\text{O}_4)_2\text{]}\cdot\text{H}_2\text{O}$  (VII);  $\text{K[Co(C}_2\text{O}_4)_3\text{]}\cdot\text{3H}_2\text{O}$  (IX); blue  $\text{K[Co(en)(C}_2\text{O}_4)_2\text{]}\cdot\text{H}_2\text{O}$  (X); violet  $\text{K[Co(en)(C}_2\text{O}_4)_2\text{]}\cdot\text{H}_2\text{O}$  (XI); and  $\text{[Co(en)(C}_2\text{O}_4)_2\text{]}\cdot\text{Cl}\cdot\text{H}_2\text{O}$  (XII). Of these, the blue and the violet varieties are probably to be regarded as new complexes, stereoisomeric with each other. Through all the procedures a green cold soln. of I was used as starting material. I was prepd. from 20 g.  $\text{KHC}_2\text{O}_4$ , 10 g.  $\text{CoCl}_2\cdot 6\text{H}_2\text{O}$  and 5 ml. 30%  $\text{H}_2\text{O}_2$  by the method described in the previous paper. To I was added 5 g. ethylenediamine carbonate (XIII), prepd. by passing  $\text{CO}_2$  into a cold aq. soln. of 70% ethylenediamine (XIV). The mixt. was placed in an ice bath for 30 min. until the green color changed to blue, and 20 ml. of abs. EtOH was added. Impure crystals sep. and were filtered off and rejected; 50 ml. addnl. EtOH was added to the filtrate, and the soln. was kept at 0° for some time. Crystals of II were collected and purified by dissolving them in a min. amt. of cold  $\text{H}_2\text{O}$  and adding abs. EtOH; 4 g. of pure II were obtained. To I was added 5 g. XIII as before and the mixt. was kept 20 min. at room temp. A violet soln. was obtained; 20 ml. EtOH was added and the soln. was stored overnight in the refrigerator. The resulting ppt. was recrystd. 3 times as before with cold  $\text{H}_2\text{O}$  and abs. EtOH to yield 6 g. III. IV was prepd. by adding 10 ml. 70% XIV to I, heating the mixt. on a water bath until the soln. became reddish yellow. After cooling, 11 g. of crude product was collected and recrystd. from  $\text{H}_2\text{O}$ . V was prepd. by adding 15 ml. 70% XIV, 3 g. KCl, and 1 g. active C to I. The mixt. was heated 30 min. on a water bath until the color changed to brownish yellow, after which C was filtered off. The filtrate was evapd. to half the initial vol., cooled, and the ppt. washed with EtOH and dried. The yield was 12 g. V. I contg. 10 g. powd.  $(\text{NH}_4)_2\text{C}_2\text{O}_4$  was warmed to 70°; when the soln. became bluish, it was cooled in an ice bath to stop further reaction and 50 ml. EtOH was added. The soln. was allowed to stand 1 hr. and the resulting crude product was collected and reprecipd. twice from the cold soln. by addn. of EtOH. The final ppt., which was washed with EtOH and  $\text{Et}_2\text{O}$  in turn, yielded 7 g. VI. The starting materials, the same as for VI, remained on a water bath until the color turned blue and finally violet; then 80 ml. EtOH was added and the soln. kept overnight in a refrigerator. The violet ppt. was collected, dissolved in small amt. of cold  $\text{H}_2\text{O}$ , and the complex was twice reprecipd. by addn. of EtOH. After the product was washed with EtOH and  $\text{Et}_2\text{O}$ , it yielded 7 g. VII. Powd.  $(\text{NH}_4)_2\text{C}_2\text{O}_4$  (5 g.) and 30 ml. concd.  $\text{NH}_4\text{OH}$  were added to I, 2 g.  $\text{NH}_4\text{Cl}$  was added, and the mixt. was warmed at 80° until the soln. became pink. The soln. was cooled, 10 ml. EtOH was added to ppt. all other salts

which were removed by filtration, and 20 ml. addnl. EtOH was added; the yield was 6 g. VIII. To a cold soln. of I was added 16 g. powd.  $(\text{CO}_2\text{H})_2$  until a bluish green soln. was obtained. The soln. was kept at 60° as long as  $\text{CO}_2$  was evolved and then was cooled, acidified with dil.  $\text{AcOH}$ , and 50 ml. EtOH was added. The yield was 12 g. IX, which was purified as usual.  $\text{K}_2\text{C}_2\text{O}_4$  (5 g.) and 5 g. ethylenediamine oxalate, prepd. by neutralizing 15 g. 70% XIV with 23 g. powd.  $(\text{CO}_2\text{H})_2$  in the cold, were poured into a cold soln. of I. The mixt. was kept about 1 hr. at room temp. until the color became bluish violet, after which it was cooled, treated with a small amt. of EtOH to remove foreign salts, and the filtrate was further treated with EtOH,  $\text{Et}_2\text{O}$ , and X. The ppt. was purified by washing with EtOH and  $\text{Et}_2\text{O}$ . XI (7 g.) was synthesized in the same way as X, except that the mixt. was heated 1 hr. instead of being left at room temp.

A mixt. of 8 g.  $(\text{CO}_2\text{H})_2$ , 2 g. KCl, and 16 ml. 70% XIV was added to I and the mixt. evapd. on a water bath until a crust formed on the surface. The soln. was cooled and the crystals were filtered and washed with EtOH and  $\text{Et}_2\text{O}$ , yielding 10 g. XII. R. E. Dunbar

The study of the Raman spectra of the system nitrosyl sulfuric acid-sulfuric acid-water with a view of denitrating highly concentrated sulfuric acid. Arthur Simon and Horst Richter (Tech. Hochschule, Dresden, Ger.). *J. prakt. Chem.* (4), 5, 68-76 (1957).—Raman spectra of vacuum distd.  $\text{H}_2\text{SO}_4$  were recorded with a 3-prism Zeiss spectrograph having a dispersion of 8A./mm. at 4358 Å and 12A./mm. at 4016 Å.  $\text{HNO}_3\text{SO}_4$  was prepd. from  $\text{NO}_2$  and  $\text{H}_2\text{SO}_4$ . The  $\text{NO}_2$  content of the nitrosic acid was detd. with a Lunge nitrometer and  $\text{H}_2\text{SO}_4$  was also detd. by the Lunge method. In the production of  $\text{H}_2\text{SO}_4$  from gypsum, nitroso acids occur which cannot be denitrated with  $\text{SO}_2$ . With the aid of Raman spectra the conditions necessary for denitrating highly concd.  $\text{H}_2\text{SO}_4$  can be established, and the reactions between the nitroso group and  $\text{SO}_2$  can be clarified. The  $\text{NO}_2$  frequency in the Raman spectrum decreases as the concn. of  $\text{H}_2\text{SO}_4$  and  $\text{NO}_2$  increases. The decrease being smaller the lower the concn. of  $\text{H}_2\text{SO}_4$ . It is shown that the depression is caused by  $\text{HSO}_3^-$ .  $\text{H}_2\text{SO}_4$  molecules (mostly assoc.) by H-bridges shield the polarizing effect of the  $\text{HSO}_3^-$  on the  $\text{NO}_2^+$  ion and thereby change its bonding condition. Attempts to denitrify show that the bonding condition of the  $\text{NO}_2^+$  ion, characterizing the position of the Raman frequency, is decisive for the denitrability of nitroso acids. George Meister

The complex formed from cobalt hydrocarbyl and butadiene. Hans B. Jonassen, Robert I. Stearns, Jouko Kenttämä, Donald W. Moore, and A. Greenville Whittaker (Tulane Univ., New Orleans, La.). *J. Am. Chem. Soc.* 79, 2586-7 (1957).—The complex formed between putadiene and Co hydrocarbyl in the absence of Oxo conditions was prepd. and the stereochem. configuration was studied. When K cobaltcarbyl was allowed to react 12 hrs. with  $\text{AcOH}$  and liquid butadiene in a high-pressure vessel, a red-brown liquid was obtained, b. 32-34° at 0.5 mm., and having the compn.  $\text{Co(CO)}_2\text{C}_4\text{H}_8$ . It is diamagnetic and contains no acidic H. The infrared and ultraviolet absorption curves indicate the disappearance of the conjugated diolefin structure and the appearance of a structure producing absorption characteristics similar to those of cis monodienes. The sharp peak at 938  $\text{cm}^{-1}$ , which in the Co hydrocarbyl has been assigned to the H vibrations, also disappears. Felix Saunders

The interaction of ammonium and potassium hexabromosulfate(IV) and liquid ammonia at 25°. II. Ammonia soluble products. George W. Watt and Lauri Vaska (Univ. of Texas, Austin). *J. Inorg. & Nuclear Chem.* 6, 249-51 (1958); cf. C.A. 53, 831b, 12942b.—Reaction of  $\text{K}_2\text{S}_2\text{O}_8$  and liquid  $\text{NH}_3$  at -25° gives  $\text{NH}_4\text{SO}_3$ , n-nitridobis(dibromotetraminesulfonium) (IV) bromide. This was isolated as the 3-hydrate and converted to n-nitridobis(dibromotetraminesulfonium) (IV) triiodide trihydrate. When  $(\text{NH}_4)_2\text{OsBr}_6$  accompanied by  $\text{NH}_4\text{Br}$  is allowed to react similarly, hexammine(manganese(II)) bromide is produced.  $\text{K}_2\text{S}_2\text{O}_8$  and  $\text{CaS}_2\text{O}_8$  accompanied hexammine(manganese(II)) hexabromosulfate(III). Jack J. Bulloff

The properties of calcium silicate hydrates. T. M. Berkovich, D. M. Kheifer, O. I. Gracheva, I. S. Zevin, and N. I. Kupreva. *Doklady Akad. Nauk S.S.S.R.* 129, 853-60 (1958).—Ca silicate hydrates  $\text{C}_3\text{S}_2\text{H}_4$ ,  $\text{C}_4\text{S}_2\text{H}_4$ ,  $\text{C}_5\text{S}_2\text{H}_4$ , and  $\text{H}$  =  $\text{H}_2\text{O}$  were synthesized. X-ray powder diagrams, electron micrographs, thermobalance, differential